

CDU CONSOLE

EW CONSOLE DISPLAY UNIT



EW CONSOLE DISPLAY UNIT

TECHNICAL SPECIFICATIONS

Display	Two 23" LCD monitors, Si/TFT technology, 1600x1200 pixels resolution, swapping function available.
Control desk	1 rugged QWERTY keyboard, 1 trackball. 1 Control Panel, 21 keys/pointers for several modes of operations. 1 audio panel with a loudspeaker, a volume control knob, a selector of the audio source and a connector for the headphone. 20W Lighting lamp.
Processor	4 schede PowerPC modules with UltraSPARC-II Processor.
RAM Memory	512 MB SDRAM.
Backplane	N.2 VME64x Bus with 2 racks overlapping.
Operating System	SUN Solaris ver.8.0, patch 21.
Graphic Processor	PCM "Dual-head" graphic adaptor, with 1 16 MB SGRAM/channel and RGB video resolution better than 1900 x 1200 pixels.
Hard disk	18,3 GB with SCSI Ultra160 interface.
DAT	N.1 DAT drive with interface SCSI for back-up data.
Additional Memory support	1 CD-R/W Driver, compatible toall formats.
Diagnostics	Built-in test equipment (BITE) with fault detection and isolation.
Power Supply	220 VAC or 115VAC, single phase, 50/60 Hz 1.5 KVA Power Consumption Distribution Unit on the front panel with ON/OFF, FAIL and TEMP. ALARM leds.

ENVIRONMENTAL REQUIREMENTS

Operating range of temperature	From 0°C to +50°C.
Humidity	MIL-STD 2036 par. 5.1.2.17.1 for inner units
Salt	More than 80% at +40°C non-condensing.
Vibration	MIL-STD-2036 par. 5.1.2.12.2.
Drip-proof	MIL-STD-167-1:14-100 Hz, Ampl. 0.2g peak.
Shock	MIL-STD-108E. 0.5 sine, 30 g for 11 milliseconds.
Safety	MIL-STD 2036 par.4.10.
EMI	MIL-STD-461E.

DIMENSIONS

Height	1841,5 mm
Width	610 mm
Depth	980 mm
Weight	160 Kg

AVAILABLE INTERFACES

- N. 70 connectors on the front and rear panels for:
- audio signals from several sources
 - blanking signals
 - seriali RS/232 e 422 serial ports
 - bias
 - "battle short"
 - fire
 - Ethernet
 - radar
 - SSR reset