



# SUPERMAC 230/D/IR

MULTIFUNCTIONAL CONSOLE FOR INFRARED  
SURVEILLANCE SYSTEM MANAGEMENT



Supplied to: GALILEO AVIONICA

## Description

**MULTIFUNCTIONAL CONSOLE FOR THE DISPLAY AND PROCESSING OF INFORMATION ABOUT IR SURVEILLANCE AND TRACKING SYSTEMS**

### TECHNICAL SPECIFICATIONS

Display	Two 23" LCD monitors, Si/TFT technology, 1600x1200 pixels resolution
Control desk	1 rugged QWERTY keyboard, 1 trackball. Can support a multifunctional keyboard
Processor	PC Pentium-III, 1,26 GHz
RAM Memory	512 MB PC-133 SDRAM
Backplane	10 slots VME64x Bus, 8 slots available
Operating System	Windows 2000 Professional with Service Pack 4 Drivers for all installed peripherals
Graphic Processor	PCM "Dual-head" graphic adaptor, with a 16 MB SGRAM/channel and RGB video resolution better than 1900 x 1200 pixels
Hard disk	147.3 GB with SCSI Ultra320 interface
Additional Memory support	1 DVD/CD-R/RW Driver, compatible to all formats. It supports 1 5.25" reader on the front panel
Floppy	1 IDE floppy driver
Diagnostics	Comprehensive built-in test equipment (BITE) with fault detection and fault isolation
Power Supply	220 VAC or 115VAC, single phase, 50/60 Hz Power Consumption 1.5 KVA Distribution Unit on the front panel with ON/OFF, FAIL and TEMP. ALARM leds

### ENVIRONMENTAL REQUIREMENTS

Operating range of temperature	From 0°C to +50°C as per MIL-STD 2036 par. 5.1.2.17.1 for inner units
Humidity	More than 80% at +40°C non-condensing
Salt	MIL-STD-2036 par. 5.1.2.12.2
Vibration	MIL-STD-167-1: 14-100 Hz, Ampl. 0.2g peak
Drip-proof	MIL-STD-108E
Shock	0.5 sine, 30 g for 11 milliseconds
Safety	MIL-STD 2036 par. 4.10
EMI	MIL-STD-461 E

### DIMENSIONS

Height	1798 mm
Width	610 mm
Depth	875 mm
Weight	175 Kg.

### INTERFACES STANDARD

- N. 3 Ethernet 100BaseTX interfaces
- N. 1 RS/422 serial port

This brochure should not be considered a contractual offer. The specifications given herein may be changed by the manufacturer, GEM elettronica, without notice.



**GEM** elettronica

marketing@gemrad.com [www.gemrad.com](http://www.gemrad.com)

